





Descripción


Collection of LED outdoor wall lights, equipped with high performance light emitting diode. Body made of aluminum injection, diffuser in PC opal. Protection against the penetration of solid and liquid particles. Allows its installation outdoors. Pre-wired luminaire



FINISHES AVAILABLE

DARK GREY MATT BLACK

ENERGY EFFICIENCY



TECHNICAL DATA SHEET

CUREAGE
SURFACE
IP65
LED 2835
12W
OSRAM
3000 / 4000 / 5000K
550
320 mA—27-40V
≥ 80
≤ 5
08
100°
100-240V ~ 50/60Hz
1
25000h. L70B50
Inside - Included
0.9
83%
Ф 171 x 300 mm
10%~90%RH
1.2
-30°~+45°
4.5 m
CE - IEC 60598-1/IEC 62031
3
High quality aluminum
PC
Anti - UV powder coating finish
Opal White

IBERLAMP reserves the right to carry out the appropriate technical modifications in order to improve the performance of the product.

We recommend consulting with the sales team to clarify any doubts.



Photometric Results

CIE Class:	Direct
Total Rated Lamp Lumens:	550 lm
Measurement Flux:	550 lm
Efficiency:	45.9 %
Downward Ratio:	45.9%
Upward Ratio:	0.0%
Luminaire Efficiency Rating (LER):	45.8
Central Intensity:	219.5 cd
Max. Intensity:	219.5 cd
Pos. Of Max Intensity:	H-1.0 V0.0
IES File Name	P-033243-30

