

BATH
DUAL SWITCH (CCT&POWER)

220-240V
50/60Hz

IP54
FRONT

LED
SMD

2K7
3K2
4K

CRI
>80

40°

UGR
<19

DRIVER
INCL.

PF
>0,7

PF
>0,8

35.000h
LIFE

TRIAC

PA
BODY

PC
LENS

AL
REFLECTOR

-20° C
40° C
-4° F
104° F

CE

SPECIFICATIONS

Version	BATH
Input voltage	220-240V
Control	Dimmable Triac
LED type	LED SMD
Driver	Included
Power (W)	6, 9
Real lumen	625-670-650,825-905-855
Color temperature	2K7-3K2-4K
CRI	CRI >80
UGR	UGR<19
Beam angle	40°
Finishes	White
Measures (mm)	106x67
Cutout hole (mm)	90x87
Weight (Kg)	0.22
Body	Polyamide
Reflector	Aluminium
Diffuser	PC Lens
IP	IP54 FRONT
Temperature range	-20°C +40°C

ACCESSORIES



PC matt black frame
Ref. 1.1063.8101



Aluminium Reflector
60°
Ref. 1.1063.8001




PC matt black passive
reflector
Ref. 1.1063.8002



PC matt silver passive
reflector
Ref. 1.1063.8003

DETAILS DESCRIPTION





Dual Switch easy
access



Interchangeable rings
and reflectors



Clips with protection