



Outdoor spotlight for ground installation

Material: luminaire in anodized anticorrosive turned aluminium /
Anti-glare shield in anodized anticorrosive extruded aluminium

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization

On request versions (additional code):

MT7 7 m cable length

Dimensions	Ø 49 x L 144 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V 50/60 Hz
Light source output	457 lm
System output	337 lm
System efficiency	84 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Weight	0.6 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION

on request:

CO CORTEN
BR BRONZE
VE GREEN

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 30°

optional optics

10 10°
54 54°

DART SPOT Ø 49 LED 4W

1618 ON3K BLACK ANODIZATION - 3000K - 30°

ACCESSORIES

