


| CRI 90
8503



Datos técnicos	
Año de realización	2018
Tipo	Luminaria de pared
Posición de instalación	Pared
Ambiente de instalación	Indoor
Fuente de luz	LED
Circuit structure	topLED
Óptica	Difusa
Light emission direction	upward
Potencia nominal	6 W DC
Poder total	7 W
Flujo luminoso (fuente)	740 lm
Tensión nominal de entrada	220 - 240 V AC
Rango de voltaje de entrada	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Índice de rendimientos cromático	90 Ra
C.C. / C.V.	AC
Clase de aislamiento	1
IP	IP20
Test del hilo incandescente	850°
Montaje directo sobre superficies normalmente inflamables	No
CE	Sí
Driver incluido.	driver
Artículo regulable	No
Orientabilidad	No
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	No
Resinado	No
Tipología de emisión luminosa	Una emisión
Peso neto	0.74 Kg
Protección descargas electrostáticas	Sí
Protección contra sobretensiones	Sí

Acabado Acabado cuerpo

Material	Hierro
Color	Text grey (R7012)
Elaboración	Pintura

Acabado Acabado difusor

Material	Policarbonato resistente a los rayos UV
Color	opalino
Elaboración	Arenado

Acabado Acabado montura

Material	Hierro
Color	Text grey (R7012)
Elaboración	Pintura

| CRI 90
8503

Single emission wall lights for indoor application. The warm white LED light source with a diffused light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 740 lm, with a 123.3 lm/W nominal luminous efficacy.



The device body is made of iron and features a text grey (r7012) finish, processed by means of coating; the diffuser is made of uv resistant polycarbonate with a sandblasting treatment; the mounting frame is made of iron, with a text grey (r7012) finish, processed by means of coating.

The ingress protection degree is IP20; the total weight is of 0.74 kg.

The total absorbed power is 7 W

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Clase de eficiencia energética	
Este producto contiene una fuente de luz de clase de eficiencia energética E.	
Características Luminotécnicas	
Light Output Ratio (LOR)	72 %
Flujo luminoso (fuente)	740 lm
Flujo luminoso de luminaria	536 lm
Consumption	7 W
Rendimiento luminoso de las luminarias	76 lm/W
Temperatura de color	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Índice de rendimientos cromático	90 Ra
Temperatura de unión (luminaria)	80
Temperatura estándar del ambiente de servicio	25°C
LED Life / Failure Ratio	
L70 B10 C0 102000h	
L90 B10 C0 55000h	
UGR	
UGR axial	28.9
UGR transversal	28.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
OPTICAL	
Óptica C0/C180	110°
Light distribution simmetry	Symmetrical