


Luminaria de pared - Plafón - Proyectores | 220-240 V | 1xGU10
51365

EAC     IK06 IP65  



Datos técnicos	
Tipo	Luminaria de pared - Superficie - Plafón - Superficie - Superficie
Posición de instalación	Pared - Techo - Piso
Ambiente de instalación	Exteriores
Bombilla incluida	No
Casquillo de la bombilla	1 x GU10
Óptica	Difusa
Clase de aislamiento	1
IP	IP65
IK	IK06
Test del hilo incandescente	850°
Montaje directo sobre superficies normalmente inflamables	Sí
CE	Sí
Artículo regulable	No
Orientabilidad	Orientabile
ángulo total (plano vertical)	180 °
ángulo total (plano horizontal)	0 °
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	No
Resinado	No
Peso neto	0.722 Kg

Acabado Acabado cuerpo	
Material	Aluminio fundido EN AB - 46100
Color	Text brilliant grey RAL 9006
Elaboración	Anodizado de poro abierto + pintado con polvo
Acabado Acabado difusor	
Material	vidrio
Color	Transparent

Luminaria de pared - Plafón - Projectores | 220-240 V | 1xGU10
51365

Single emission wall lights, wall lights, ceiling downlights, ceiling downlights or projectors for outdoor application. Compatibility: LED lamp; lamp cap 1xGU10.

The device body is made of die-cast aluminium en ab - 46100 and features a text brilliant grey ral 9006 finish, processed by means of open pore anodizing + powder coating; the diffuser is made of glass. Surface treatment of the product body through aluminum chemical conversion, followed by polyester powder coating, using exclusively coatings compliant with the Qualicoat standard.

The ingress protection degree is IP65; the total weight is of 0.722 kg.

The device features protection class I and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Vision_WJ | Projectors | Accessories

51365



Piquete

posición de instalación: terreno, Material de revestimiento: pc

Code

50370