

Luminaria de pie | 220-240 V | 1xE27

16150



Ø 280

Datos técnicos	
Tipo	Luminaria de pie
Posición de instalación	Piso
Ambiente de instalación	Exteriores
Bombilla incluida	No
Casquillo de la bombilla	1 x E27
Light emission direction	upward
Frequency	50-60 Hz
Óptica	Difusa
Clase de aislamiento	2
IP	IP65
IK	IK10
Test del hilo incandescente	650°
Montaje directo sobre superficies normalmente inflamables	Sí
CE	Sí
Artículo regulable	No
Orientabilidad	No
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	Sí
Enchufe eléctrico	Type F
Largo del cable	5 m
Resinado	No
Peso neto	1.300 Kg

Acabado Acabado difusor	
Material	PE
Color	Natural polyethylene

Acabado Acabado montura	
Material	PC
Color	blanco

Luminaria de pie | 220-240 V | 1xE27
16150

Double emission floor lamp for outdoor application. Compatibility: LED lamp; lamp cap 1xE27.

Product suitable for installations in coastal areas with high salinity and strong exposure to atmospheric agents.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish.


The ingress protection degree is IP65; the total weight is of 1.300 kg.

The power supply cable is included and features a 5 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Características Luminotécnicas	
Light Output Ratio (LOR)	79 %
Flujo luminoso de luminaria	634 lm
Consumption	14 W
Rendimiento luminoso de las luminarias	57 lm/W
Temperatura de unión (luminaria)	80
Flujo luminoso (fuente)	1 x lm
OPTICAL	
Óptica C0/C180	180°
Light distribution simmetry	Symmetrical



Luminaria de pie | 220-240 V | 1xE27

16150

Double emission floor lamp for outdoor application. Compatibility: LED lamp; lamp cap 1xE27.

Product suitable for installations in coastal areas with high salinity and strong exposure to atmospheric agents.

The diffuser is made of pe; the mounting frame is made of PC, with a white finish.


The ingress protection degree is IP65; the total weight is of 1.300 kg.

The power supply cable is included and features a 5 m length.

The device features protection class II and can be floor-mounted with an outer casing, code 14930(for concrete or masonry).


Compliant with the EN 60598-1 standard and its specific provisions.

Oh!_FL65 E27 | Floor Lamp | Accessories
16150



Caja de empotrar - caja de empotrar para instalación en el suelo o en el cemento

Code
14930



Piquete

posición de instalación: terreno, Material de revestimiento: policarbonato resistente a los rayos uv

Code
14931



Conector

Code
14992